

Solar & Screen

AURORA SUMMER

Design Coloured - Dichroic

Description

With its dichroic and chameleon-like properties, the self-adhesive Aurora film changes in hue and colour with every variation in angle of observation. The Aurora decorative film uses natural light to maximum effect, bringing your windows and glass partitions to life through its warm tones dichroic tint.







AURORA SUMMER

Design Coloured - Dichroic

Characteristics



Warranty

5 years



Fire Resistance Rating

M1

Storage in recommended conditions
3 years



REACH / RoHS

Compliant



Widths Available

135 cm



Installation Type Interior



Color From the Outside

Warm Colour



Length 30.5 m



Product Carbon Footprint (LCA)

 $1.26 \ kgCO2e/m^2$

Construction

- Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 2 High optical quality dyed polyester
- 3 Bonding adhesive
- 4 High optical quality polyester
- 5 PS adhesive, polymerizes with glass within 15
- 6 Protection PET release liner, disposable after installation



Composition

PET



Thickness

55 µm

Optical and solar properties

UV Rejection (%)	95
Visible Light Transmission (%)	72
Glue	Pressure sensitive acrylic

Application advice


Vertical situation and for a standard glazed surface

× Not recommended

Caution

Clear Single Pane	✓
Tinted Single Pane	į.
Reflective Tinted Single Pane	✓
Clear Double Pane	į
Tinted Double Pane	į.
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	į.
Stadip Ext. Clear Double Pane	į
Stadip Int. Clear Double Pane	×

Details



Installation and Maintenance Advise

Use Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Access the installation and maintenance advice video