



Solar  Screen

CLEAR 4 XC

Safety
Security - Prevention

Description

Clear 4 XC film secures your windows and prevents broken glass from scattering in the event of an impact. Perfectly transparent and easy to apply.

Certifications



REACH / RoHS
Compliant



Fire Resistance Rating
M1



View test videos on
the safety film

Characteristics



Warranty
5 years



Fire Resistance Rating
M1



Storage in recommended conditions
3 years



REACH / RoHS
Compliant



Widths Available
122 cm, 152 cm, 183 cm



Installation Type
Exterior



Color From the Outside
Transparent



Length
30.5 m



Product Carbon Footprint (LCA)
2.42 kgCO₂e/m²

Construction

- 1 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 2 High optical quality polyester
- 3 Reinforced PS adhesive to accompany the elasticity of the film in case of impact, polymerizes with glass within 30 days
- 4 Protection PET release liner, disposable after installation



Composition
PET



Thickness
120 μm

Mechanical Properties



Tensile force at break
28 kg/cm



Elongation at break
125%

Optical and solar properties

Pane type	Single 3mm		Double Low-E	
	No film	With Film	No film	With Film
UV Rejection (%)	25	99	40	99
Visible Light Transmission (%)	91	91	82	82
Visible Light Reflection - External (%)	8	8	11	11
Visible Light Reflection - Internal (%)	8	8	12	11
Solar Energy Reflection (%)	5	10	28	28
Solar Energy Absorption (%)	8	8	12	18
Solar Energy Transmission (%)	87	82	60	54
Total Solar Energy Rejected (%)	12	17	35	39
Glare Reduction (%)	-	8	-	1
Shading Coefficient	-	0.90	-	0.94
g-value	0.88	0.83	0.65	0.61
U-value (W/m ² .°C)	5.8	5.7	1.1	1.1

Application advice⁰¹

Vertical situation and for a standard glazed surface

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not recommended ! Caution

Installation and Maintenance Advise

Safety film with reinforced PS adhesive, requiring a suitable application solution : Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water, and a suitable safety squeegee (150-054 / 150-055 / 150-056). Do not clean for at least one month or apply stickers/adhesives to the film.



Download the
installation and
maintenance advice

⁰¹ Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.

The data in this information sheet is not contractual, SOLAR SCREEN reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.