



Solar Screen

CLEAR 4 XC G

Safety
Anti-Graffiti - Long term

Description

Clear 4 XC G solvent resistant films provide highly effective protection against tags and graffiti. Its protective qualities are not limited to solvents, it will also shield a window's surface from other acts of vandalism involving scratching or acid etching. An easy film to install and replace, it is also classed as a security film, providing protection by holding shattered glass in place in the event of an explosion or serious impact.

Certifications



REACH / RoHS
Compliant



EN 12600
2B2













Fire Resistance Rating
M1



View test videos on
the safety film

Characteristics

-  **Warranty**
5 years
-  **Fire Resistance Rating**
M1
-  **Storage in recommended conditions**
3 years
-  **REACH / RoHS**
Compliant
-  **EN 12600**
2B2
-  **Widths Available**
122 cm, 152 cm, 183 cm
-  **Installation Type**
Exterior
-  **Color From the Outside**
Transparent
-  **Length**
30.5 m
-  **Product Carbon Footprint (LCA)**
2.44 kgCO₂e/m²

Mechanical Properties


-  **Tensile force at break**
220 kg/cm
-  **Elongation at break**
125%

Optical and solar properties

Pane type	Single 3mm		Double Low-E	
	No film	With Film	No film	With Film
UV Rejection (%)	25	99	40	99
Visible Light Transmission (%)	91	91	82	81
Visible Light Reflection - External (%)	8	9	11	10
Visible Light Reflection - Internal (%)	8	9	12	10
Solar Energy Reflection (%)	5	10	28	28
Solar Energy Absorption (%)	8	8	12	18
Solar Energy Transmission (%)	87	82	60	54
Total Solar Energy Rejected (%)	12	17	35	39
Glare Reduction (%)	-	14	-	1
Shading Coefficient	-	0.90	-	0.94
g-value	0.88	0.83	0.65	0.61
U-value (W/m ² .°C)	5.8	5.7	1.1	1.1

Construction

- 1 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 2 High optical quality polyester
- 3 Bonding adhesive
- 4 High optical quality polyester
- 5 Half permanent adhesive that will ease the removal of the film from the window
- 6 Protection PET release liner, disposable after installation

-  **Composition**
PET
-  **Thickness**
125 µm

Application advice⁰¹

Vertical situation and for a standard glazed surface

- Clear Single Pane** ✓
- Tinted Single Pane** ✓
- Reflective Tinted Single Pane** ✓
- Clear Double Pane** ✓
- Tinted Double Pane** ✓
- Reflective Tinted Double Pane** ✓
- Gas-Filled Double Pane - Low E** ✓
- Stadip Ext. Clear Double Pane** ✓
- Stadip Int. Clear Double Pane** ✓

✓ Yes ✗ Not recommended ! Caution

Installation and Maintenance Advise

Safety film with reinforced PS adhesive, requiring a suitable application solution : Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water, and a suitable safety squeegee (150-054 / 150-055 / 150-056). Do not clean for at least one month or apply stickers/adhesives to the film.



Download the installation and maintenance advice

⁰¹ Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.

The data in this information sheet is not contractual, SOLAR SCREEN reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.