



Solar  Screen

CLEAR AB Anti-Fog

Safety

Specialty - Anti Fog

Description

Clear AB Anti Fog film helps prevent windows and mirrors from fogging up in situations where ambient temperatures may vary significantly, such as in bathrooms, swimming pools, saunas, cold-rooms, etc.

Certifications



REACH / RoHS
Compliant












Fire Resistance Rating
M1



View test videos on
the safety film

Characteristics


-  **Warranty**
2 years
-  **Fire Resistance Rating**
M1
-  **Storage in recommended conditions**
3 years
-  **REACH / RoHS**
Compliant
-  **Widths Available**
152 cm
-  **Installation Type**
Interior
-  **Color From the Outside**
Transparent
-  **Length**
30.5 m
-  **Product Carbon Footprint (LCA)**
1.23 kgCO₂e/m²

Construction

- 1 Protection PET release liner, disposable after installation
- 2 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 3 High optical quality polyester
- 4 Reinforced PS adhesive to accompany the elasticity of the film in case of impact, polymerizes with glass within 30 days
- 5 Protection PET release liner, disposable after installation

-  **Composition**
PET
-  **Thickness**
100 µm

Mechanical Properties

-  **Tensile strength at break**
N/A
-  **Elongation at break**
N/A

Optical and solar properties

Pane type	Single 3mm		Double Low-E	
	No film	With Film	No film	With Film
UV Rejection (%)	25	99	40	99
Visible Light Transmission (%)	91	87	82	79
Visible Light Reflection - External (%)	8	11	11	16
Visible Light Reflection - Internal (%)	8	11	12	16
Solar Energy Reflection (%)	5	10	12	24
Solar Energy Absorption (%)	8	14	28	26
Solar Energy Transmission (%)	87	76	60	50
Total Solar Energy Rejected (%)	12	18	35	35
Glare Reduction (%)	-	14	-	4
Shading Coefficient	-	0.90	-	1.0
g-value	0.88	0.82	0.65	0.65

Application advice⁰¹

Vertical situation and for a standard glazed surface

- Clear Single Pane** ✓
- Tinted Single Pane** ✓
- Reflective Tinted Single Pane** ✓
- Clear Double Pane** ✓
- Tinted Double Pane** ✓
- Reflective Tinted Double Pane** ✓
- Gas-Filled Double Pane - Low E** ✓
- Stadip Ext. Clear Double Pane** ✓
- Stadip Int. Clear Double Pane** ✓

✓ Yes ✗ Not recommended ! Caution

Installation and Maintenance Advise

Use Slide On (600-FO2) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Download the
installation and
maintenance advice

⁰¹ Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.
The data in this information sheet is not contractual, SOLAR SCREEN reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.