



Solar  Screen

MAT BLUE PET

Design
Coloured - Mat










Description

Applied to clear glass, the Mat Blue film bestows a mat blue tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.



Discover the product
through video

Characteristics

-  **Warranty**
5 years
-  **Fire Resistance Rating**
M1
-  **Storage in recommended conditions**
3 years
-  **REACH / RoHS**
Compliant
-  **Widths Available**
152 cm
-  **Installation Type**
Interior
-  **Color From the Outside**
Blue
-  **Length**
30.5 m
-  **Product Carbon Footprint (LCA)**
1.26 kgCO₂e/m²

Optical and solar properties

UV Rejection (%)	95
Visible Light Transmission (%)	55
Glue	Pressure sensitive acrylic

Application advice

Vertical situation and for a standard glazed surface

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗


✓ Yes ✗ Not recommended ! Caution

Construction

- 1 Frosted polyester with satin surface
- 2 Bonding adhesive
- 3 High optical quality dyed polyester
- 4 PS adhesive, polymerizes with glass within 15 days
- 5 Protection PET release liner, disposable after installation

-  **Composition**
PET
-  **Thickness**
60 µm

Details



Installation and Maintenance Advise

Use Slide On (600-FO2) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Access the installation and maintenance advice video