



Solar  Screen

MAT SILVER PVC










Design

Privacy - MAT PVC base

Description

Mat Silver PVC privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.

Characteristics

-  **Warranty**
5 years
-  **Fire Resistance Rating**
M1
-  **Storage in recommended conditions**
3 years
-  **REACH / RoHS**
Compliant
-  **Widths Available**
122 cm, 152 cm
-  **Installation Type**
Exterior
-  **Color From the Outside**
Depoli
-  **Length**
50 m
-  **Product Carbon Footprint (LCA)**
1.26 kgCO2e/m²

Construction

- 75 µm cast PVC
- Half Permanent Adhesive, allowing the degassing of the actual surface, and limits the adhesive transfer during removal
- Paper release liner allowing digital cutting

-  **Composition**
PVC
-  **Thickness**
75 µm

Optical and solar properties

UV Rejection (%)	95
Visible Light Transmission (%)	60
Glue	Pressure sensitive acrylic


Application advice

Vertical situation and for a standard glazed surface

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not recommended ! Caution

Details



Installation and Maintenance Advise

Use Slide On (600-FO2) or Film On (600-F0355) diluted at 2 cL/L of water for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Access the installation and maintenance advice video