



Solar Screen

MULTI - PROTEC 4 C

Safety

Anti-Graffiti - Standard

Description

This multi-layer film has many lives! Indeed, thanks to its 4 layers of 100 microns, it will protect your surfaces from graffiti and tags. Once the film is too visually damaged, you can simply remove the layer. You have 4 layers before you have to install a new film. In addition, this film will also reinforce your windows against accidents, aggression and explosion risks.

Certifications



REACH / RoHS
Compliant



Fire Resistance Rating
M1



View test videos on
the safety film

Characteristics

-  **Warranty**
5 years
-  **Fire Resistance Rating**
M1
-  **Storage in recommended conditions**
3 years
-  **REACH / RoHS**
Compliant
-  **Widths Available**
152 cm
-  **Installation Type**
Exterior
-  **Color From the Outside**
Transparent
-  **Length**
30.5 m
-  **Product Carbon Footprint (LCA)**
2.64 kgCO₂e/m²

Construction

- 1 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 2 100 µm high optical quality polyester
- 3 Non permanent PS adhesive
- 4 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 5 100 µm high optical quality polyester
- 6 Non permanent PS adhesive
- 7 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 8 100 µm high optical quality polyester
- 9 Non permanent PS adhesive
- 10 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 11 100 µm high optical quality polyester
- 12 Non permanent PS adhesive
- 13 Protection PET release liner, disposable after installation

-  **Composition**
PET
-  **Thickness**
485 µm

Mechanical Properties

-  **Tensile force at break**
N/A
-  **Elongation at break**
N/A

Optical and solar properties

Pane type	Single 3mm		Double Low-E	
	No film	With Film	No film	With Film
UV Rejection (%)	25	98	40	99
Visible Light Transmission (%)	91	82	82	74
Visible Light Reflection - External (%)	8	11	11	16
Visible Light Reflection - Internal (%)	8	11	12	16
Solar Energy Reflection (%)	5	9	28	24
Solar Energy Absorption (%)	8	14	12	25
Solar Energy Transmission (%)	87	77	60	50
Total Solar Energy Rejected (%)	12	19	35	35
Glare Reduction (%)	-	17	-	10
Shading Coefficient	-	0.90	-	1.0
g-value	0.88	0.83	0.65	0.65
U-value (W/m ² .°C)	5.8	5.7	1.1	1.1

Application advice⁰¹

Vertical situation and for a standard glazed surface

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not recommended ! Caution

Installation and Maintenance Advise

Safety film with reinforced PS adhesive, requiring a suitable application solution : Slide On (600-F02) or Film On (600-F0355) diluted at 2 cL/L of water, and a suitable safety squeegee (150-054 / 150-055 / 150-056). Do not clean for at least one month or apply stickers/adhesives to the film.



Download the
installation and
maintenance advice

⁰¹ Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.

The data in this information sheet is not contractual, SOLAR SCREEN reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.