

Solar Screen

PROTEC 6 C

Safety

Anti-Graffiti - Standard

Description

Protec 6 C solvent resistant films provide highly effective protection against tags and graffiti. The film's protective qualities are not limited to solvents, it will also shield a window's surface from other acts of vandalism involving scratching or acid etching. An easy film to install and replace, it is also classed as a security film, providing protection by holding shattered glass in place in the event of an explosion, impact or fire.

Certifications

REACH / RoHS
Compliant

Fire Resistance Rating
M1

Certified B Corporation

View test videos on the safety film

Solar Screen

PROTEC 6 C

Safety
Anti-Graffiti - Standard

Characteristics

Warranty
Up to 5 years

Fire Resistance Rating
M1

Storage in recommended conditions
3 years

REACH / RoHS
Compliant

Widths Available
152 cm

Installation Type
Interior / Exterior

Color From the Outside
Transparent

Length
30.5 m

Product Carbon Footprint (LCA)
2.48 kgCO2e/m²

Construction

1 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
2 High optical quality polyester
3 Half permanent adhesive that will ease the removal of the film from the window
4 Protection PET release liner, disposable after installation

Composition
PET

Thickness
180 µm

Mechanical Properties

Tensile force at break
N/A

Elongation at break
125%

Optical and solar properties

	Single 3mm		Double Low-E	
Pane type	No film	With Film	No film	With Film
UV Rejection (%)	25	95	40	99
Visible Light Transmission (%)	**91**	**86**	**82**	**78**
Visible Light Reflection - External (%)	8	11	11	16
Visible Light Reflection - Internal (%)	8	11	12	16
Solar Energy Reflection (%)	5	10	28	24
Solar Energy Absorption (%)	8	8	12	22
Solar Energy Transmission (%)	87	83	60	54
Total Solar Energy Rejected (%)	**12**	**20**	**35**	**35**
Glare Reduction (%)	-	14	-	5
Shading Coefficient	-	0.90	-	1.0
g-value	**0.88**	**0.83**	**0.65**	**0.65**
U-value (W/m².°C)	5.8	5.7	1.1	1.1

Application advice[01]

Vertical situation and for a standard glazed surface

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes × Not recommended ! Caution

Installation and Maintenance Advise

Safety film with reinforced PS adhesive, requiring a suitable application solution : Slide On (600-FO2) or Film On (600-F0355) diluted at 2 cL/L of water, and a suitable safety squeegee (150-054 / 150-055 / 150-056). Do not clean for at least one month or apply stickers/adhesives to the film.

Download the installation and maintenance advice

01 Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.
The data in this information sheet is not contractual, SOLAR SCREEN reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.