


Solar Screen

SECUR 4

Safety

Specialty - Emergency Glass Repair

Description

Mirrors in public spaces, such as sports facilities, swimming pools and lifts must comply with higher than ordinary glass safety and security requirements. The Secur 4 (50m) film is specially designed to be applied to the back of mirrors, providing protection by holding shattered glass in place in the event of an explosion, fire or impact.

Certifications

REACH / RoHS
Compliant

EN 12600
2B2

Fire Resistance Rating
M1

Certified B Corporation

View test videos on the safety film

Solar Screen

SECUR 4

Safety
Specialty - Emergency Glass Repair

Characteristics

Warranty
Up to 5 years

Fire Resistance Rating
M1

Storage in recommended conditions
3 years

REACH / RoHS
Compliant

EN 12600
2B2

Widths Available
150 cm

Installation Type
Interior

Color From the Outside
Transparent

Length
50 m

Product Carbon Footprint (LCA)
1.82 kgCO2e/m²

Construction

1 Polyester 100 µm
2 Reinforced PS adhesive to accompany the elasticity of the film in case of impact, polymerizes with glass within 30 days
3 Paper release liner allowing digital cutting

Composition
PET

Thickness
125 µm

Mechanical Properties

Tensile force at break
220 kg/cm

Elongation at break
125%

Optical and solar properties

	Single 3mm		Double Low-E	
Pane type	No film	With Film	No film	With Film
UV Rejection (%)	25	95	40	99
Visible Light Transmission (%)	**91**	**85**	**82**	**77**
Visible Light Reflection - External (%)	8	11	11	16
Visible Light Reflection - Internal (%)	8	11	12	16
Solar Energy Reflection (%)	5	9	28	24
Solar Energy Absorption (%)	8	14	12	25
Solar Energy Transmission (%)	87	77	60	50
Total Solar Energy Rejected (%)	**12**	**19**	**35**	**35**
Glare Reduction (%)	-	14	-	6
Shading Coefficient	-	0.9	-	1
g-value	**0.88**	**0.83**	**0.65**	**0.65**
U-value (W/m².°C)	5.8	5.7	1.1	1.1

Application advice[01]

Vertical situation and for a standard glazed surface

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes × Not recommended ! Caution

Installation and Maintenance Advise

Safety film with reinforced PS adhesive, requiring a suitable application solution : Slide On (600-FO2) or Film On (600-F0355) diluted at 2 cL/L of water, and a suitable safety squeegee (150-054 / 150-055 / 150-056). Do not clean for at least one month or apply stickers/adhesives to the film.

Download the installation and maintenance advice

01 Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.
The data in this information sheet is not contractual, SOLAR SCREEN reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.